


PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : A61B 5/00, A61M 5/172		A1	(11) International Publication Number: WO 00/19887
			(43) International Publication Date: 13 April 2000 (13.04.00)
(21) International Application Number: PCT/US99/21703		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 20 September 1999 (20.09.99)			
(30) Priority Data: 60/103,812 8 October 1998 (08.10.98) US 09/377,472 19 August 1999 (19.08.99) US			
(71) Applicant: MINIMED INC. [US/US]; 12744 San Fernando Road, Sylmar, CA 91342 (US).			
(72) Inventors: MANN, Alfred, E.; 14175 Mulholland Drive, Beverly Hills, CA 90210 (US). PURVIS, Richard, E.; 991 Palm Terrace, Pasadena, CA 91104 (US). MASTROTARO, John, J.; 10642 Lindbrook Drive, Los Angeles, CA 90024 (US). CAUSEY, James, D.; 2107 Cushman Court, Simi Valley, CA 93063 (US). HENKE, James; 5105 E. Los Angeles Avenue, PMB 168, Simi Valley, CA 93063 (US). HONG, Peter; 28030 Kenton Lane, Santa Clarita, CA 91350 (US). LIVINGSTON, John, H.; 31 Augusta Lane, Newport Beach, CA 92660 (US). HAGUE, Clifford, W.; 14570 Benefit Street, No. 303, Sherman Oaks, CA 91403 (US).			
(74) Agent: KOVELMAN, Paul, H.; MiniMed, Inc., 12744 San Fernando Road, Sylmar, CA 91342 (US).			
Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>			

(54) Title: **TELEMETERED CHARACTERISTIC MONITOR SYSTEM**

(57) Abstract

A telemetered characteristic monitor system includes a remotely located data receiving device, a sensor for producing signal indicative of a characteristic of a user, and a transmitter device. The transmitter device includes a housing, a sensor connector, a processor, and a transmitter. The transmitter receives the signals from the sensor and wirelessly transmits the processed signals to the remotely located data receiving device. The processor coupled to the sensor processes the signals from the sensor for transmission to the remotely located data receiving device. The data receiving device may be a characteristic monitor, a data receiver that provides data to another device, an RF programmer for a medical device, a medication delivery device (such as an infusion pump), or the like.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

TELEMETERED CHARACTERISTIC MONITOR SYSTEM

This application claims priority on U.S. Provisional Application Serial No. 60/103,812 filed on October 8, 1998 and U.S. Patent Application Serial No. 09/377,472 filed on August 19, 1999, which is specifically incorporated by reference herein.

5

FIELD OF THE INVENTION

This invention relates to telemetered subcutaneous sensor devices and, in particular embodiments, to devices and methods for wireless communication between an implantable subcutaneous sensor set at a selected insertion site within the body of a user and a remotely
10 located characteristic monitor.

BACKGROUND OF THE INVENTION

Over the years, a variety of implantable electrochemical sensors have been developed for detecting and/or quantifying specific agents or compositions in a patient's blood. For
15 instance, glucose sensors have been developed for use in obtaining an indication of blood glucose levels in a diabetic patient. Such readings are useful in monitoring and/or adjusting a treatment regimen which typically includes the regular administration of insulin to the patient. Thus, blood glucose readings improve medical therapies with semi-automated medication infusion pumps of the external type, as generally described in U.S. Patent Nos. 4,562,751;
20 4,678,408; and 4,685,903; or automated implantable medication infusion pumps, as generally described in U.S. Patent No. 4,573,994, which are herein incorporated by reference.

Generally, small and flexible electrochemical sensors can be used to obtain periodic readings over an extended period of time. In one form, flexible subcutaneous sensors are constructed in accordance with thin film mask techniques in which an elongated sensor
25 includes thin film conductive elements encased between flexible insulative layers of polyimide sheets or similar material. Such thin film sensors typically include a plurality of exposed electrodes at one end for subcutaneous placement with a user's interstitial fluid, blood, or the like, and a corresponding exposed plurality of conductive contacts at another end for convenient external electrical connection with a suitable monitoring device through a wire
30 or cable. Typical thin film sensors are described in commonly assigned U.S. Patent Nos. 5,390,671; 5,391,250; 5,482,473; and 5,586,553 which are incorporated by reference herein.

See also U.S. Patent No. 5,299,571.

Drawbacks to the use of implantable sensors arise from the use of a wired connection between the implantable sensor set and the monitor. The use of the wire or cable is an additional inconvenience to users that already utilize an external infusion pump that includes an infusion insertion set and tube to infuse the medication. Also, the preferred site for some sensing device may be inconvenient for connection by wire to a characteristic monitor. For implantable pumps, the wire or cable negates the very benefit of having an internal device without external wires or cables. For Type 2 diabetics, who do not necessarily need or use an infusion pump, the use of a cable is seen as an inconvenience that may inhibit use of the device. In addition, the use of a wire or cable limits a user's ability to position the monitor, since it can be placed no further away than the ultimate length of the wire or cable. Thus, the user must normally wear the monitor, which can be problematic. For example, removal of the monitor for sleeping can be difficult, since a user would tend to become "tangled" in the wire or cable, between the sensor and the monitor, during the normal tossing and turning that occurs during sleep. Furthermore, the more connections the user must deal with (e.g., infusion pump and catheter and/or monitor with wire to sensor), the more complicated it is to use the devices, and the less likely the user will maintain compliance with the medical regimen due to perceived and actual difficulties with all of the wires and cables.

20 SUMMARY OF THE DISCLOSURE

It is an object of an embodiment of the present invention to provide an improved telemetered implantable sensor set (such as a subcutaneous or percutaneous sensor) and monitor connection device, which obviates for practical purposes, the above mentioned limitations.

25 According to an embodiment of the invention, a telemetered characteristic monitor system includes a remotely located data receiving device, a sensor for producing signal indicative of a characteristic of a user, and a transmitter device. In preferred embodiments, the transmitter device includes a housing, a sensor connector, a processor, and a transmitter. A potentiostat within the transmitter device may be coupled to the sensor connector and
30 applies power to the sensor. The sensor connector receives the produced signals from the sensor. The processor is coupled to the sensor connector and processes the signals from the

sensor for delivery to the remotely located data receiving device. The transmitter is coupled to the processor for wirelessly transmitting the processed signals to the remotely located data receiving device. In preferred embodiments, the data receiving device is a characteristic monitor. However, in other embodiments, the data receiving device is a data receiver that provides data to another device, an RF programmer, a medication delivery device (such as an infusion pump), or the like.

In particular embodiments, the transmitter of the transmitter device transmits the processed signals by radio frequencies. In other embodiments, the sensor may be implanted in and/or through subcutaneous, dermal, sub-dermal, intra-peritoneal or peritoneal tissue, and the sensor connector of the transmitter device includes a cable that is connected to the sensor. Also, the implantable sensor can be configured for a wired connection to a characteristic monitor, and the sensor connector of the transmitter device is formed to connect to the configured implantable sensor. Still further embodiments of the transmitter device include a receiver to receive data and instructions from the characteristic monitor, or the like.

Embodiments of the transmitter device (when used with a subcutaneous or percutaneous sensor) may include a bio-compatible adhesive to secure the housing to a skin surface of the user. Preferably, the housing of the transmitter device is less than about 3.0 inches in diameter by 0.5 inches thick. In addition, the housing is resistant to fluids when immersed in a fluid, operable in a temperature range of 0°C to 50°C, and has an operable life of at least 3 months. If the sensor is fully implanted, the transmitter that is connected to the sensor may be secured by sutures, sewing rings, or the like.

Other features and advantages of the invention will become apparent from the following detailed description, taken in conjunction with the accompanying drawings which illustrate, by way of example, various features of embodiments of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

A detailed description of embodiments of the invention will be made with reference to the accompanying drawings, wherein like numerals designate corresponding parts in the several figures.

Fig. 1 is a perspective view illustrating a subcutaneous sensor insertion set and telemetered characteristic monitor transmitter device embodying the novel features of the

invention;

Fig. 2 is an enlarged longitudinal vertical section taken generally on the line 2-2 of Fig. 1;

Fig. 3 is an enlarged longitudinal sectional of a slotted insertion needle used in the insertion set of Figs. 1 and 2;

Fig. 4 is an enlarged transverse section taken generally on the line 4-4 of Fig. 3;

Fig. 5 is an enlarged transverse section taken generally on the line 5-5 of Fig. 3;

Fig. 6 is an enlarged fragmented sectional view corresponding generally with the encircled region 6 of Fig. 2; and

Fig. 7 is an enlarged transverse section taken generally on the line 7-7 of Fig. 2.

Fig. 8(a) is a top plan and partial cut-away view of the telemetered characteristic monitor transmitter device in accordance with the embodiment shown in Fig. 1.

Fig. 8(b) is a simplified block diagram of the printed circuit board of the telemetered characteristic monitor transmitter device in accordance with the embodiments shown in Fig. 1.

Fig. 9 is a timing diagram illustrating an embodiment of a message and timing format used by the telemetered characteristic monitor transmitter device shown in Fig. 1.

Fig. 10 is a simplified block diagram of a characteristic monitor used in accordance with an embodiment of the present invention.

Fig. 11 is a timing diagram for the characteristic monitor shown in Fig. 10.

Fig. 12 is another timing diagram for the characteristic monitor shown in Fig. 10.

Fig. 13 is a simplified block diagram of a telemetered characteristic monitor transmitter and sensor set system in accordance with another embodiment of the present invention.

Fig. 14 is a simplified block diagram of a telemetered characteristic monitor transmitter and characteristic monitor system in accordance with still another embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

As shown in the drawings for purposes of illustration, the invention is embodied in a telemetered characteristic monitor transmitter coupled to a sensor set, that may be implanted in and/or through subcutaneous, dermal, sub-dermal, inter-peritoneal or peritoneal tissue, that

transmits data from the sensor set to the characteristic monitor for determining body characteristics. In preferred embodiments of the present invention, the sensor set and monitor are for determining glucose levels in the blood and/or body fluids of the user without the use of, or necessity of, a wire or cable connection between the transmitter and the monitor.

5 However, it will be recognized that further embodiments of the invention may be used to determine the levels of other agents, characteristics or compositions, such as hormones, cholesterol, medication concentrations, pH, oxygen saturation, viral loads (e.g., HIV), or the like. In other embodiments, the sensor set may also include the capability to be programmed or calibrated using data received by the telemetered characteristic monitor transmitter device,
10 or may be calibrated at the monitor device (or receiver). The telemetered characteristic monitor system is primarily adapted for use in subcutaneous human tissue. However, still further embodiments may be placed in other types of tissue, such as muscle, lymph, organ tissue, veins, arteries or the like, and used in animal tissue. Embodiments may provide sensor readings on an intermittent or continuous basis.

15 The telemetered characteristic monitor system 1, in accordance with a preferred embodiment of the present invention include a percutaneous sensor set 10, a telemetered characteristic monitor transmitter device 100 and a characteristic monitor 200. The percutaneous sensor set 10 utilizes an electrode-type sensor, as described in more detail below. However, in alternative embodiments, the system may use other types of sensors, such
20 as chemical based, optical based or the like. In further alternative embodiments, the sensors may be of a type that is used on the external surface of the skin or placed below the skin layer of the user. Preferred embodiments of a surface mounted sensor would utilize interstitial fluid harvested from underneath the skin. The telemetered characteristic monitor transmitter 100 generally includes the capability to transmit data. However, in alternative embodiments, the
25 telemetered characteristic monitor transmitter 100 may include a receiver, or the like, to facilitate two-way communication between the sensor set 10 and the characteristic monitor 200. The characteristic monitor 200 utilizes the transmitted data to determine the characteristic reading. However, in alternative embodiments, the characteristic monitor 200 may be replaced with a data receiver, storage and/or transmitting device for later processing of
30 the transmitted data or programming of the telemetered characteristic monitor transmitter 100.

In addition, a relay or repeater 4 may be used with a telemetered characteristic monitor

transmitter 100 and a characteristic monitor 200 to increase the distance that the telemetered characteristic monitor transmitter 100 can be used with the characteristic monitor 200, as shown in Fig. 13. For example, the relay 4 could be used to provide information to parents of children using the telemetered characteristic monitor transmitter 100 and the sensor set 10 from a distance. The information could be used when children are in another room during sleep or doing activities in a location remote from the parents. In further embodiments, the relay 4 can include the capability to sound an alarm. In addition, the relay 4 may be capable of providing telemetered characteristic monitor transmitter 100 data from the sensor set 10, as well as other data, to a remotely located individual via a modem connected to the relay 4 for display on a monitor, pager or the like. The data may also be downloaded through a Communication-Station 8 to a remotely located computer 6 such as a PC, lap top, or the like, over communication lines, by modem or wireless connection, as shown in Fig. 14. Also, some embodiments may omit the Communication Station 8 and uses a direct modem or wireless connection to the computer 6. In further embodiments, the telemetered characteristic monitor transmitter 100 transmits to an RF programmer, which acts as a relay, or shuttle, for data transmission between the sensor set 10 and a PC, laptop, Communication-station, a data processor, or the like. In further alternatives, the telemetered characteristic monitor transmitter 100 may transmit an alarm to a remotely located device, such as a communication-station, modem or the like to summon help. In addition, further embodiments may include the capability for simultaneous monitoring of multiple sensors and/or include a sensor for multiple measurements.

Still further embodiments of the telemetered characteristic monitor transmitter 100 may have and use an input port for direct (e.g., wired) connection to a programming or data readout device and/or be used for calibration of the sensor set 10. Preferably, any port would be water proof (or water resistant) or include a water proof, or water resistant, removable cover.

The purpose of the telemetered characteristic monitor system 1 (see Fig. 2) is to provide for better treatment and control in an outpatient or a home use environment. For example, the monitor system 1 can provide indications of glucose levels, a hypoglycemia/hyperglycemia alert and outpatient diagnostics. It is also useful as an evaluation tool under a physician's supervision.

The monitor system 1 also removes inconvenience by separating the monitor electronics into two separate devices; a telemetered characteristic monitor transmitter 100, which attaches to the implantable sensor set 10; and a characteristic monitor 200 (or other receiver), which is carried like a pager. This provides several advantages over wire connected devices. For instance, the user can more easily conceal the presence of the monitor system 1, since a wire will not be visible (or cumbersome), within clothing. Such remote communication also provides greater convenience and flexibility in the placement of the sensor. It also makes it is easier to protect the characteristic monitor 200, which can be removed from the user's body during showers, exercise, sleep or the like. In addition, the use of multiple components (e.g., transmitter 100 and characteristic monitor 200) facilitates upgrades or replacements, since one module or the other can be modified or replaced without requiring complete replacement of the monitor system 1. Further, the use of multiple components can improve the economics of manufacturing, since some components may require replacement on a more frequent basis, sizing requirements may be different for each module, there may be different assembly environment requirements, and modifications can be made without affecting the other components.

The telemetered characteristic monitor transmitter 100 takes characteristic information, such as glucose data or the like, from the percutaneous sensor set 10 and transmits it via wireless telemetry to the characteristic monitor 200, which displays and logs the received glucose readings. Logged data can be downloaded from the characteristic monitor 200 to a personal computer, laptop, or the like, for detailed data analysis. In further embodiments, the telemetered characteristic monitor system 1 may be used in a hospital environment or the like. Still further embodiments of the present invention may include one or more buttons (on the telemetered characteristic monitor transmitter 100 or characteristic monitor 200) to record data and events for later analysis, correlation, or the like. In addition, the telemetered characteristic monitor transmitter 100 may include a transmit on/off button for compliance with safety standards and regulations to temporarily suspend transmissions. Further buttons can include a sensor on/off button to conserve power and to assist in initializing the sensor set 10. The telemetered characteristic monitor transmitter 100 and characteristic monitor 200 may also be combined with other medical devices to combine other patient data through a common data network and telemetry system.

Further embodiments of the percutaneous sensor set 10 would monitor the temperature of the sensor set 10, which can then be used to improve the calibration of the sensor. For instance, for a glucose sensor, the enzyme reaction activity may have a known temperature coefficient. The relationship between temperature and enzyme activity can be used to adjust the sensor values to more accurately reflect the actual characteristic levels. In addition to temperature measurements, the oxygen saturation level can be determined by measuring signals from the various electrodes of the sensor set 10. Once obtained, the oxygen saturation level may be used in calibration of the sensor set 10 due to changes in the oxygen saturation levels, and its effects on the chemical reactions in the sensor set 10. For instance, as the oxygen level goes lower the sensor sensitivity may be lowered. The oxygen level can be utilized in calibration of the sensor set 10 by adjusting for the changing oxygen saturation. In alternative embodiments, temperature measurements may be used in conjunction with other readings to determine the required sensor calibration.

As shown in Figs. 1-7, a percutaneous sensor set 10 is provided for subcutaneous placement of an active portion of a flexible sensor 12 (see Fig. 2), or the like, at a selected site in the body of a user. The subcutaneous or percutaneous portion of the sensor set 10 includes a hollow, slotted insertion needle 14, and a cannula 16. The needle 14 is used to facilitate quick and easy subcutaneous placement of the cannula 16 at the subcutaneous insertion site. Inside the cannula 16 is a sensing portion 18 of the sensor 12 to expose one or more sensor electrodes 20 to the user's bodily fluids through a window 22 formed in the cannula 16. After insertion, the insertion needle 14 is withdrawn to leave the cannula 16 with the sensing portion 18 and the sensor electrodes 20 in place at the selected insertion site.

In preferred embodiments, the percutaneous sensor set 10 facilitates accurate placement of a flexible thin film electrochemical sensor 12 of the type used for monitoring specific blood parameters representative of a user's condition. Preferably, the sensor 12 monitors glucose levels in the body, and may be used in conjunction with automated or semi-automated medication infusion pumps of the external or implantable type as described in U.S. Pat. Nos. 4,562,751; 4,678,408; 4,685,903 or 4,573,994, to control delivery of insulin to a diabetic patient.

Preferred embodiments of the flexible electrochemical sensor 12 are constructed in accordance with thin film mask techniques to include elongated thin film conductors

embedded or encased between layers of a selected insulative material such as polyimide film or sheet, and membranes. The sensor electrodes 20 at a tip end of the sensing portion 18 are exposed through one of the insulative layers for direct contact with patient blood or other body fluids, when the sensing portion 18 (or active portion) of the sensor 12 is subcutaneously placed at an insertion site. The sensing portion 18 is joined to a connection portion 24 (see Fig. 2) that terminates in conductive contact pads, or the like, which are also exposed through one of the insulative layers. In alternative embodiments, other types of implantable sensors, such as chemical based, optical based, or the like, may be used.

As is known in the art, and illustrated schematically in Fig. 2, the connection portion 24 and the contact pads are generally adapted for a direct wired electrical connection to a suitable monitor 200 for monitoring a user's condition in response to signals derived from the sensor electrodes 20. Further description of flexible thin film sensors of this general type are be found in U.S. Patent. No. 5,391,250, entitled METHOD OF FABRICATING THIN FILM SENSORS, which is herein incorporated by reference. The connection portion 24 may be conveniently connected electrically to the monitor 200 or a telemetered characteristic monitor transmitter 100 by a connector block 28 (or the like) as shown and described in U.S. Pat. No. 5,482,473, entitled FLEX CIRCUIT CONNECTOR, which is also herein incorporated by reference. Thus, in accordance with embodiments of the present invention, subcutaneous sensor sets 10 are configured or formed to work with either a wired or a wireless characteristic monitor system.

The proximal part of the sensor 12 is mounted in a mounting base 30 adapted for placement onto the skin of a user. As shown, the mounting base 30 is a pad having an underside surface coated with a suitable pressure sensitive adhesive layer 32, with a peel-off paper strip 34 normally provided to cover and protect the adhesive layer 32, until the sensor set 10 is ready for use. As shown in Figs. 1 and 2, the mounting base 30 includes upper and lower layers 36 and 38, with the connection portion 24 of the flexible sensor 12 being sandwiched between the layers 36 and 38. The connection portion 24 has a forward section joined to the active sensing portion 18 of the sensor 12, which is folded angularly to extend downwardly through a bore 40 formed in the lower base layer 38. In preferred embodiments, the adhesive layer 32 includes an anti-bacterial agent to reduce the chance of infection; however, alternative embodiments may omit the agent. In the illustrated embodiment, the

mounting base is generally rectangular, but alternative embodiments may be other shapes, such as circular, oval, hour-glass, butterfly, irregular, or the like.

The insertion needle 14 is adapted for slide-fit reception through a needle port 42 formed in the upper base layer 36 and further through the lower bore 40 in the lower base layer 38. As shown, the insertion needle 14 has a sharpened tip 44 and an open slot 46 which extends longitudinally from the tip 44 at the underside of the needle 14 to a position at least within the bore 40 in the lower base layer 36. Above the mounting base 30, the insertion needle 14 may have a full round cross-sectional shape, and may be closed off at a rear end of the needle 14. Further description of the needle 14 and the sensor set 10 are found in U.S. Patent No. 5,586,553, entitled "TRANSCUTANEOUS SENSOR INSERTION SET" and co-pending U.S. Patent Application Serial No. 08/871,831, entitled 'DISPOSABLE SENSOR INSERTION ASSEMBLY,' which are herein incorporated by reference.

The cannula 16 is best shown in Figs. 6 and 7, and includes a first portion 48 having partly-circular cross-section to fit within the insertion needle 14 that extends downwardly from the mounting base 30. In alternative embodiments, the first portion 48 may be formed with a solid core; rather than a hollow core. In preferred embodiments, the cannula 16 is constructed from a suitable medical grade plastic or elastomer, such as polytetrafluoroethylene, silicone, or the like. The cannula 16 also defines an open lumen 50 in a second portion 52 for receiving, protecting and guideably supporting the sensing portion 18 of the sensor 12. The cannula 16 has one end fitted into the bore 40 formed in the lower layer 38 of the mounting base 30, and the cannula 16 is secured to the mounting base 30 by a suitable adhesive, ultrasonic welding, snap fit or other selected attachment method. From the mounting base 30, the cannula 16 extends angularly downwardly with the first portion 48 nested within the insertion needle 14, and terminates before the needle tip 44. At least one window 22 is formed in the lumen 50 near the implanted end 54, in general alignment with the sensor electrodes 20, to permit direct electrode exposure to the user's bodily fluid when the sensor 12 is subcutaneously placed. Alternatively, a membrane can cover this area with a porosity that controls rapid diffusion of glucose through the membrane.

As shown in Figs. 1, 2 and 8(a), the telemetered characteristic monitor transmitter 100 is coupled to a sensor set 10 by a cable 102 through a connector 104 that is electrically coupled to the connector block 28 of the connector portion 24 of the sensor set 10. In

alternative embodiments, the cable 102 may be omitted, and the telemetered characteristic monitor transmitter 100 may include an appropriate connector (not shown) for direct connection to the connector portion 24 of the sensor set 10 or the sensor set 10 may be modified to have the connector portion 24 positioned at a different location, such as for example, on the top of the sensor set 10 to facilitate placement of the telemetered characteristic monitor transmitter over the subcutaneous sensor set 10. This would minimize the amount of skin surface covered or contacted by medical devices, and tend to minimize movement of the sensor set 10 relative to the telemetered characteristic monitor transmitter 100. In further alternative embodiments, the cable 102 and the connector 104 may be formed as add-on adapters to fit different types of connectors on different types or kinds of sensor sets. The use of adapters would facilitate adaptation of the telemetered characteristic monitor transmitter 100 to work with a wide variety of sensor systems. In further embodiments, the telemetered characteristic monitor transmitter 100 may omit the cable 102 and connector 104 and is instead optically couple with an implanted sensor, in the subcutaneous, dermal, sub-dermal, inter-peritoneal or peritoneal tissue, to interrogate the implanted sensor using visible, and/or IR frequencies, either transmitting to and receiving a signal from the implanted sensor or receiving a signal from the implanted sensor.

The telemetered characteristic monitor 100 (also known as Potentiostat Transmitter Device) includes a housing 106 that supports a printed circuit board 108, batteries 110, antenna 112, and the cable 102 with the connector 104. In preferred embodiments, the housing 106 is formed from an upper case 114 and a lower case 116 that are sealed with an ultrasonic weld to form a waterproof (or resistant) seal to permit cleaning by immersion (or swabbing) with water, cleaners, alcohol or the like. In preferred embodiments, the upper and lower case 114 and 116 are formed from a medical grade plastic. However, in alternative embodiments, the upper case 114 and lower case 116 may be connected together by other methods, such as snap fits, sealing rings, RTV (silicone sealant) and bonded together, or the like, or formed from other materials, such as metal, composites, ceramics, or the like. In other embodiments, the separate case can be eliminated and the assembly is simply potted in epoxy or other moldable materials that is compatible with the electronics and reasonably moisture resistant. In preferred embodiments, the housing 106 is disk or oval shaped. However, in alternative embodiments, other shapes, such as hour glass, rectangular or the like, may be

used. Preferred embodiments of the housing 106 are sized in the range of 2.0 square inches by 0.35 inches thick to minimize weight, discomfort and the noticeability of the telemetered characteristic monitor transmitter 100 on the body of the user. However, larger or smaller sizes, such as 1.0 square inches and 0.25 inches thick or less, and 3.0 square inches and 0.5 inches thick or more, may be used. Also, the housing may simply be formed from potted epoxy, or other material, especially if the battery life relative to the device cost is long enough, or if the device is rechargeable.

As shown, the lower case 116 may have an underside surface coated with a suitable pressure sensitive adhesive layer 118, with a peel-off paper strip 120 normally provided to cover and protect the adhesive layer 118, until the sensor set telemetered characteristic monitor transmitter 100 is ready for use. In preferred embodiments, the adhesive layer 118 includes an anti-bacterial agent to reduce the chance of infection; however, alternative embodiments may omit the agent. In further alternative embodiments, the adhesive layer 118 may be omitted and the telemetered characteristic monitor transmitter 100 is secured to the body by other methods, such as an adhesive overdressing, straps, belts, clips or the like.

In preferred embodiments, the cable 102 and connector 104 are similar to (but not necessarily identical to) shortened versions of a cable and connector that are used to provide a standard wired connection between the sensor set 10 and the characteristic monitor 200. This allows the telemetered characteristic monitor transmitter 100 to be used with existing sensor sets 10, and avoids the necessity to re-certify the connector portion 24 of the sensor set 10 for use with a wireless connection. The cable 102 should also include a flexible strain relief portion (not shown) to minimize strain on the sensor set 10 and prevent movement of the inserted sensor 12, which can lead to discomfort or dislodging of the sensor set 10. The flexible strain relief portion is intended to minimize sensor artifacts generated by user movements that might cause the sensing area of the sensor set 10 to move relative to the body tissues in contact with the sensing area of the sensor set 10.

The printed circuit board 108 of the telemetered characteristic monitor transmitter 100 includes a sensor interface 122, processing electronics 124, timers 126, and data formatting electronics 128, as shown in Fig. 8(b). In preferred embodiments, the sensor interface 122, processing electronics 124, timers 126, and data formatting electronics 128 are formed as separate semiconductor chips; however, alternative embodiments may combine the various

semiconductor chips into a single customized semiconductor chip. The sensor interface 122 connects with the cable 102 that is connected with the sensor set 10. In preferred embodiments, the sensor interface is permanently connected to the cable 102. However, in alternative embodiments, the sensor interface 122 may be configured in the form of a jack to accept different types of cables that provide adaptability of the telemetered characteristic monitor transmitter 100 to work with different types of sensors and/or sensors placed in different locations of the user's body. In preferred embodiments, the printed circuit board 108, and associated electronics, are capable of operating in a temperature range of 0° C and 50° C. However, larger or smaller temperature ranges may be used.

Preferably, the battery assembly will use a weld tab design to connect power to the system. For example, it can use three series silver oxide 357 battery cells 110, or the like. However, it is understood that different battery chemistries may be used, such as lithium based chemistries, alkaline batteries, nickel metalhydride, or the like, and different numbers of batteries can be used. In further embodiments, the sensor interface 122 will include circuitry and/or a mechanism for detecting connection to the sensor set 10. This would provide the capability to save power and to more quickly and efficiently start initialization of the sensor set 10. In preferred embodiments, the batteries 110 have a life in the range of 3 months to 2 years, and provide a low battery warning alarm. Alternative embodiments may provide longer or shorter battery lifetimes, or include a power port, solar cells or an inductive coil to permit recharging of rechargeable batteries in the telemetered characteristic monitor transmitter 100.

In preferred embodiments, the telemetered characteristic monitor transmitter 100 provides power, through the cable 102 and cable connector 104 to the sensor set 10. The power is used to monitor and drive the sensor set 10. The power connection is also used to speed the initialization of the sensor 12, when it is first placed under the skin. The use of an initialization process can reduce the time for sensor 12 stabilization from several hours to an hour or less. The preferred initialization procedure uses a two step process. First, a high voltage (preferably between 1.0-1.2 volts - although other voltages may be used) is applied to the sensor 12 for 1 to 2 minutes (although different time periods may be used) to allow the sensor 12 to stabilize. Then, a lower voltage (preferably between 0.5-0.6 volts - although other voltages may be used) is applied for the remainder of the initialization process (typically 58 minutes or less). Other stabilization/initialization procedures using differing currents,

currents and voltages, different numbers of steps, or the like, may be used. Other embodiments may omit the initialization/stabilization process, if not required by the sensor or if timing is not a factor.

At the completion of the stabilizing process, a reading may be transmitted from the sensor set 10 and the telemetered characteristic monitor transmitter 100 to the characteristic monitor 200, and then the user will input a calibrating glucose reading into characteristic monitor 200. In alternative embodiments, a fluid containing a known value of glucose may be injected into the site around the sensor set 10, and then the reading is sent to the characteristic monitor 200 and the user inputs the known concentration value, presses a button (not shown) or otherwise instructs the monitor to calibrate using the known value. During the calibration process, the telemetered characteristic monitor transmitter 100 checks to determine if the sensor set 10 is still connected. If the sensor set 10 is no longer connected, the telemetered characteristic monitor transmitter 100 will abort the stabilization process and sound an alarm (or send a signal to the characteristic monitor 200 to sound an alarm).

Preferably, the transmissions (or telemetry) of the telemetered characteristic monitor transmitter 100 will contain at least the following information: a unique ID code that uniquely identifies each telemetered characteristic monitor transmitter 100, a sensor characteristic data signal representative of the measured characteristic value (e.g., glucose or the like) from the sensor 18 of the subcutaneous sensor set 10, a counter electrode voltage, a low battery flag, and error detection bits (such as CRC). Fig. 9 and Table 1 illustrate a preferred message format for the telemetry of the telemetered characteristic monitor transmitter 100. However, it will be understood that different message protocols and structures may be used.

1.	Encoding method: OOK MANCHESTER (1=1/0, 0=0/1 sequence, where 1 = transmitter (TX) on)
2.	Clock rate 1024 Hz (512Hz symbol/bit rate).
3.	Message format:
5	Preamble: 4 bits (0101, want only one transition per bit)
	Message Type: 4 bits (1010 = transmitter 100, 15 others for pump/ppc protocol)
	Unique ID #: 16 bits (65536 unique numbers)
	Message count #: 4 bits (also determines TX time slot)
10	Working Electrode: 12 bits (9MSBs + 3 magnitude bits = 16bit range – converted by the characteristic monitor 200 into a value representative of characteristic level, such as glucose level)
	Low battery flag: 1 bit (0=ok, 1=low)
	Counter Voltage: 7 bits (0-1.2V typ., 8bit a/d 3.2V FS)
	CRC: 8 bits
15	Total 56 bits (x 1/512hz = 109 mS)
4.	Message TX interval: 300 seconds (5 min) + 1-16 seconds pseudo-random delay (TX time slot)
5.	TX duty cycle: $56\text{bits} \times 1/512\text{Hz} \times 1/300\text{S} \times 1/2 = 1.823\text{e-}4$

20 Table 1. Message format

Preferred embodiments utilize a time-slicing transmission protocol. Use of the time slicing protocol facilitates the use of multiple signals on the same frequency bands or to the same receiver from multiple transmitters. The time-slicing may also be used to obviate the need for a receiver in the telemetered characteristic monitor transmitter 100. For instance, the use of intermittent transmission reduces the amount of power required to operate the transmitter 100 and to extend the life of the device. It also saves power in the characteristic monitor 200 by reducing the amount of time the characteristic monitor 200 must spend in the receive mode.

30 In preferred embodiments, when the telemetered characteristic monitor transmitter 100 is connected to the sensor set 10, it detects the connection and is activated. Next, if desired or necessary, the telemetered characteristic monitor transmitter 100 initializes the sensor 12 of the sensor set 10. After (or in some cases during) initialization, the telemetered characteristic monitor transmitter 100 sends out a message of between 100-150 ms length every 5 minutes. 35 Although other timing intervals ranging from 1 second to 30 minutes may be used.

Preferably, the message is transmitted in a pseudo-randomly selected time window within the 128 seconds following the 5 minute interval. In preferred embodiments, the telemetered characteristic transmitter 100 utilizes its own unique ID as a random-seed to set up a table of transmission time windows that defines the order in which the telemetered

characteristic monitor 100 will transmit a message following the 5 minute interval. The order is repeated after the table is set-up. Included in the message sent will be the message count number, which indicates where in the sequence of time windows the telemetered characteristic monitor transmitter is currently transmitting. The characteristic monitor 200 uses the unique ID code of the telemetered characteristic monitor transmitter 100 to set up a corresponding table in the characteristic monitor 200 and the received message count to synchronize the characteristic monitor 200 with the current position in the table being used by the telemetered characteristic monitor transmitter 100 to predict the next time window to be used. The use of pseudo-random time windows prevents multiple transmitters from continuously interfering with other transmitting devices that are temporarily, or inadvertently, synchronized with the telemetered characteristic monitor transmitter 100. The characteristic monitor 200 acquires the transmitted message, and determines the time window in which the characteristic monitor 200 must be in a receive mode to acquire the next message. The characteristic monitor 200 then places itself in the receive mode every 5 minutes (although other timing intervals from 1 second to 30 minutes may be used) to receive the next message and data from the telemetered characteristic monitor transmitter 100 at the next predicted time window. Thus, the characteristic monitor 200 needs only be in the receive mode for 1 second (i.e., 1 time window); rather than 128 seconds (128 time windows). In alternative embodiments, the characteristic monitor 200 may not use the unique ID and the message count and may remain in the receive mode during the entire period (e.g., for 128 time windows) during which a transmission is possible. In addition, other embodiments may cause the characteristic monitor 200 to enter the receive mode 1 time window ahead and stay on for 1 time window longer to maximize the likelihood of receiving the next transmission. In further alternative embodiments, the telemetered characteristic monitor transmitter 100 and/or characteristic monitor 200 may utilize other methods or numbers to determine when transmission time windows are selected. Alternative message time-slicing transmission parameters, such as message length, number of time windows, frequency of transmissions, or the like, that are larger or smaller than those describe above, may also be used. Preferred embodiments transmit the data and/or information at a data rate between 1000 Hz to 4000 Hz modulated onto a high frequency carrier wave. However, alternative embodiments may use smaller or larger transmission rates, with the rate being selected based on user environment, power

requirements, interference issues, redundancy criteria, or the like.

If a transmitted message is not received by the characteristic monitor 200 after a predetermined period of time, an alarm will be sounded or provided. In addition, the characteristic monitor 200 may continue to attempt to receive the next message by entering
5 the receive mode at the next anticipated transmission time or may expand to enter the receive mode to cover all time windows until the next message is received.

In another alternative embodiment, if there is little or no likelihood of interference from other telemetered characteristic monitor transmitter 100, such as by message length, frequency selections or the like, the telemetered characteristic monitor transmitter 100 may
10 transmit at one time window for all cases (typically the choice of window may be randomly selected at connection of a sensor set 10 or set at the factory). This permits the characteristic monitor 200 to be in the receive mode for even shorter periods of time (i.e., approximately 200 ms to bracket the telemetered characteristic monitor transmitter 100 transmission instead of the 128 seconds (or 1 second if able to predict the next time window) needed to bracket 128
15 windows) to conserve power in the characteristic monitor 200. For instance, in this scenario, the characteristic monitor 200 will be in a non-receive mode for 299.8 seconds and in a receive mode for 200 ms. In particular embodiments the non-receive mode and receive mode periods will be determined by the message length and expected frequency of transmission. It is also noted that in a system where the receiver must cover a range of time windows, the
20 receiver may lock on to a particular range of time windows to permit the receiver being in the receive mode for shorter periods of time.

The use of these transmission protocols obviates the need for a transmitter and receiver in both the telemetered characteristic monitor transmitter 100 and characteristic monitor 200, which reduces costs, simplifies the system design, reduces power consumption and the like.
25 However, alternative embodiments may include the capability for two-way communication, if desirable. In further embodiments, the telemetered characteristic monitor transmitter 100 transmits continuously and the characteristic monitor 200 enters the receive mode when desired or required to determine a characteristic value, such as a glucose level or the like.

In preferred embodiments, the telemetered characteristic monitor transmitter 100 will
30 have the ability to uniquely identify itself to the characteristic monitor 200. The telemetered characteristic monitor transmitter 100 will have an operating range to the characteristic

monitor 200 of at least 10 feet. In alternative embodiments, larger or smaller ranges may be used, with the selection being dependent on the environment in which the telemetered characteristic monitor transmitter 100 will be used, the size and needs of the user, power requirements, and the like.

5 In further alternative embodiments, the telemetered characteristic monitor transmitter 100 can be combined with a sensor set 10 as a single unit. This would be particularly well adapted where batteries and the transmitter can be made cheaply enough to facilitate changing the transmitter 100 with each new sensor set 10.

10 As shown in Fig. 10, the characteristic monitor 200 includes a telemetry receiver 202, a Telemetry Decoder (TD) 204 and a host micro-controller (Host) 206 for communication with the telemetered characteristic monitor transmitter 100. The TD 204 is used to decode a received telemetry signal from the transmitter device and forward the decoded signal to the Host 206. The Host 206 is a microprocessor for data reduction, data storage, user interface, or the like. The telemetry receiver 202 receives the characteristic data (e.g., glucose data) from
15 the telemetered characteristic monitor transmitter, and passes it to the TD 204 for decoding and formatting. After complete receipt of the data by the TD 204, the data is transferred to the Host 206 for processing, where calibration information, based upon user entered characteristic readings (e.g., blood glucose readings), is performed to determine the corresponding characteristic level (e.g., glucose level) from measurement in the characteristic data (e.g.,
20 glucose data). The Host 206 also provides for storage of historical characteristic data, and can download the data to a personal computer, lap-top, or the like, via a com-station, wireless connection, modem or the like. For example, in preferred embodiments, the counter electrode voltage is included in the message from the telemetered characteristic monitor transmitter 100 and is used as a diagnostic signal. The raw current signal values generally range from 0 to
25 999, which represents sensor electrode current in the range between 0.0 to 99.9 nanoAmperes, and is converted to characteristic values, such as glucose values in the range of 40 to 400 mg/dl. However, in alternative embodiments, larger or smaller ranges may be used. The values are then displayed on the characteristic monitor 200 or stored in data memory for later recall.

30 The characteristic monitor 200 also includes circuitry in the TD 204 to uniquely mate it to an identified telemetered characteristic monitor transmitter 100. In preferred

embodiments, the identification number of the telemetered characteristic monitor transmitter 100 is entered manually by the user using keys located on the characteristic monitor 200. In alternative embodiments, the characteristic monitor 200 includes a "learn ID" mode.

Generally, the "learn ID" mode is best suited for the home environment, since multiple

5 telemetered characteristic monitor transmitters 100, typically encountered in a hospital setting, are less likely to cause confusion in the characteristic monitor 200 when it attempts to learn an ID code. In addition, the characteristic monitor 200 will include the ability to learn or be reprogrammed to work with a different (or replacement) telemetered characteristic monitor transmitter 100. The preferred operating distance is at least 10 feet. In alternative
10 embodiments, larger or smaller ranges may be used, with the selection being dependent on the environment in which the telemetered characteristic monitor transmitter 100 will be used, the size and needs of the user, power requirements, and the like. Furthermore, if the characteristic monitor 200 does not receive a transmission from the identified telemetered characteristic monitor transmitter 100 after a certain period of time (e.g., one or more missed transmissions),
15 an alarm will be sounded.

In preferred embodiments, the characteristic monitor 200 utilizes a two processor system, in which the Host 206 is the master processor and the TD 204 is a slave processor dedicated to telemetry processing. A first communication protocol between the Host 206 and the TD 204 is shown in Fig. 11. The first protocol uses a serial peripheral interface (SPI) 208
20 and two control lines 210 and 212; one control line (chip select - CSPIC) 210 is used by Host 206 to wake up the TD 204 to initiate telemetry receiving task; and the other control line (data ready - DR) 212 is used by the TD 204 to indicate to the Host 206 that the telemetry data from the telemetered characteristic monitor transmitter has been received and is ready to be transferred to the HC08 206. Upon receiving data through the SPI 208, the Host 206 sends an
25 acknowledgment through the SPI 208 to the TD 204. In preferred embodiments, fixed length data blocks are used. However, in alternative embodiments, variable length data blocks may be used. In preferred embodiments, the Host 206 may pull the Chip Select (CSPIC) 210 high at any time to abort the telemetry data transfer from the TD 204. Alternatively, an additional line (not shown) may be used to reset the TD 204. Fig. 12 shows a second, more complex,
30 alternative protocol that is used by the Host 206 and the TD 204.

In alternative embodiments, the TD 204 and Host 206 may be combined together in a

single semiconductor chip to obviate the need for dual processors and to reduce the space needed for the electronics. In further embodiments, the functions of the TD 204 and Host 206 may be allocated differently between one or more processors.

As shown in Fig. 2, the characteristic monitor may include a display 214 that is used to display the results of the measurement received from the sensor 18 in the sensor set 10 via the telemetered characteristic monitor transmitter 100. The results and information displayed includes, but is not limited to, trending information of the characteristic (e.g., rate of change of glucose), graphs of historical data, average characteristic levels (e.g., glucose), or the like. Alternative embodiments include the ability to scroll through the data. The display 214 may also be used with buttons (not shown) on the characteristic monitor to program or update data in the characteristic monitor 200. It is noted that the typical user can be expected to have somewhat diminished visual and tactile abilities due to complications from diabetes or other conditions. Thus, the display 214 and buttons should be configured and adapted to the needs of a user with diminished visual and tactile abilities. In alternative embodiments, the value can be conveyed to the user by audio signals, such as beeps, speech or the like. Still further embodiments may use a touch screen instead of (or in some cases addition to) buttons to facilitate water proofing and to ease changes in the characteristic monitor 200 hardware to accommodate improvements or upgrades.

Preferably, the characteristic monitor uses batteries (not shown) to provide power to the characteristic monitor. For example, a plurality of silver oxide batteries may be used. However, it is understood that different battery chemistries may be used, such as lithium based, alkaline based, nickel metalhydride, or the like, and different numbers of batteries can be used. In preferred embodiments, the batteries have a life in the range of 1 month to 2 years, and provide a low battery warning alarm. Alternative embodiments may provide longer or shorter battery lifetimes, or include a power port, solar cells or an induction coil to permit recharging of rechargeable batteries in the characteristic monitor 200. In preferred embodiments, the batteries are not replaceable to facilitate waterproofing the housing 106.

In further embodiments of the present invention, the characteristic monitor 200 may be replaced by a different device. For example, in one embodiment, the telemetered characteristic monitor transmitter 100 communicates with an RF programmer (not shown) that is also used to program and obtain data from an infusion pump or the like. The RF

programmer may also be used to update and program the transmitter 100, if the transmitter 100 includes a receiver for remote programming, calibration or data receipt. The RF programmer can be used to store data obtained from the sensor 18 and then provide it to either an infusion pump, characteristic monitor, computer or the like for analysis. In further
5 embodiments, the transmitter 100 may transmit the data to a medication delivery device, such as an infusion pump or the like, as part of a closed loop system. This would allow the medication delivery device to compare sensor results with medication delivery data and either sound alarms when appropriate or suggest corrections to the medication delivery regimen. In preferred embodiments, the transmitter 100 would include a transmitter to receive updates or
10 requests for additional sensor data. An example of one type of RF programmer can be found in U.S. Patent Application Serial No. 60/096,994 filed August 18, 1998 and is entitled "INFUSION DEVICE WITH REMOTE PROGRAMMING, CARBOHYDRATE CALCULATOR AND/OR VIBRATION ALARM CAPABILITIES," or U.S. Patent Application Serial No. 09/334,858 filed June 17, 1999 and is entitled "EXTERNAL
15 INFUSION DEVICE WITH REMOTE PROGRAMMING, BOLUS ESTIMATOR AND/OR VIBRATION ALARM CAPABILITIES," both of which are herein incorporated by reference.

In further embodiments, the telemetered characteristic monitor transmitter can include a modem, or the like, to transfer data to and from a healthcare professional. Further embodiments, can receive updated programming or instructions via a modem connection.

20 In use, the sensor set 10 permits quick and easy subcutaneous placement of the active sensing portion 18 at a selected site within the body of the user. More specifically, the peel-off strip 34 (see Fig. 1) is removed from the mounting base 30, at which time the mounting base 30 can be pressed onto and seated upon the patient's skin. During this step, the insertion needle 14 pierces the user's skin and carries the protective cannula 16 with the sensing portion
25 18 to the appropriate subcutaneous placement site. During insertion, the cannula 16 provides a stable support and guide structure to carry the flexible sensor 12 to the desired placement site. When the sensor 12 is subcutaneously placed, with the mounting base 30 seated upon the user's skin, the insertion needle 14 can be slidably withdrawn from the user. During this withdrawal step, the insertion needle 14 slides over the first portion 48 of the protective
30 cannula 16, leaving the sensing portion 18 with electrodes 20 directly exposed to the user's body fluids via the window 22. Further description of the needle 14 and the sensor set 10 are

found in U.S. Patent No. 5,586,553, entitled "TRANSCUTANEOUS SENSOR INSERTION SET"; co-pending U.S. Patent Application Serial No. 08/871,831, entitled "DISPOSABLE SENSOR INSERTION ASSEMBLY"; and co-pending U.S. Patent Application Serial No. 09/161,128, filed September 25, 1998, entitled "A SUBCUTANEOUS IMPLANTABLE
5 SENSOR SET HAVING THE CAPABILITY TO REMOVE OR DELIVER FLUIDS TO AN INSERTION SITE," which are herein incorporated by reference.

Next, the user connects the connection portion 24 of the sensor set 10 to the cable 102 of the telemetered characteristic monitor transmitter 100, so that the sensor 12 can then be used over a prolonged period of time for taking blood chemistry or other characteristic
10 readings, such as blood glucose readings in a diabetic patient. Preferred embodiments of the telemetered characteristic monitor transmitter 100 detect the connection of the sensor 12 to activate the telemetered characteristic monitor transmitter 100. For instance, connection of the sensor 12 may activate a switch or close a circuit to turn the telemetered characteristic monitor transmitter 100 on. The use of a connection detection provides the capability to
15 maximize the battery and shelf life of the telemetered characteristic monitor transmitter prior to use, such as during manufacturing, test and storage. Alternative embodiments of the present invention may utilize an on/off switch (or button) on the telemetered characteristic monitor transmitter 100.

The transmitter 100 is then affixed to the user's body with an adhesive overdressing.
20 Alternatively, the peel-off strip 34 (see Fig. 1) is removed from the lower case 116, at which time the lower case 116 can be pressed onto and seated upon the patient's skin. The user then activates the transmitter 100, or the transmitter is activated by detection of the connection to the sensor 12 of the sensor set 10. Generally, the act of connecting (and disconnecting) the sensor 12 activates (and deactivates) the telemetered characteristic monitor 100, and no other
25 interface is required. In alternative steps, the sensor set 10 is connected to the transmitter 100 prior to placement of the sensor 12 to avoid possible movement or dislodging of the sensor 12 during attachment of the transmitter 100. Also, the transmitter may be attached to the user prior to attaching the sensor set 10 to the transmitter 100.

The user then programs the characteristic monitor (or it learns) the identification of the
30 transmitter 100 and verifies proper operation and calibration of the transmitter 100. The characteristic monitor 200 and transmitter 100 then work to transmit and receive sensor data

to determine characteristic levels. Thus, once a user attaches a transmitter 100 to a sensor set 10, the sensor 12 is automatically initialized and readings are periodically transmitted, together with other information, to the characteristic monitor 200.

After a sensor set 10 has been used for a period of time, it is replaced. The user will
5 disconnect the sensor set 10 from the cable 102 of the telemetered characteristic monitor transmitter 100. In preferred embodiments, the telemetered characteristic monitor transmitter 100 is removed and posited adjacent the new site for a new sensor set 10. In alternative embodiments, the user does not need to remove the transmitter 100. A new sensor set 10 and sensor 12 are attached to the transmitter 100 and connected to the user's body. Monitoring
10 then continues, as with the previous sensor 12. If the user must replace the telemetered characteristic monitor transmitter 100, the user disconnects the transmitter 100 from the sensor set 10 and the user's body. The user then connects a new transmitter 100, and reprograms the characteristic monitor (or learns) to work with the new transmitter 100. Monitoring then continues, as with the previous sensor 12.

15 Additional embodiments of the present invention may include a vibrator alarm (or optional indicator such as an L.E.D.) in either or both the telemetered characteristic monitor transmitter 100 and the characteristic monitor 200 to provide a tactile (vibration) alarm to the user, such as sensor set malfunction, improper connection, low battery, missed message, bad data, transmitter interference, or the like. The use of a vibration alarm provides additional
20 reminders to an audio alarm, which could be important with someone suffering an acute reaction, or to have non-audio alarms to preserve and conceal the presence of the telemetered characteristic monitor system 1.

While the description above refers to particular embodiments of the present invention, it will be understood that many modifications may be made without departing from the spirit
25 thereof. The accompanying claims are intended to cover such modifications as would fall within the true scope and spirit of the present invention.

The presently disclosed embodiments are therefore to be considered in all respects as illustrative and not restrictive, the scope of the invention being indicated by the appended claims, rather than the foregoing description, and all changes which come within the meaning
30 and range of equivalency of the claims are therefore intended to be embraced therein.

WHAT IS CLAIMED IS:

1. A telemetered characteristic monitor system for monitoring a characteristic of a user, the system comprising:
 - a remotely located data receiving device;
 - 5 a sensor for producing a signal indicative of the characteristic of the user; and
 - a transmitter device including:
 - a housing;
 - a sensor connector coupled to the housing and that is connectable to the sensor to receive signals from the sensor;
 - 10 a processor within the housing coupled to the sensor connector to process the signals from the sensor for delivery to the remotely located data receiving device; and
 - a transmitter coupled to the processor for wirelessly transmitting the processed signals to the remotely located data receiving device.
- 15 2. A telemetered characteristic monitor system according to claim 1, wherein the transmitter transmits the processed signals by radio frequencies.
3. A telemetered characteristic monitor system according to claim 1, wherein the sensor is implantable in tissue selected from the group consisting essentially of subcutaneous,
20 dermal, sub-dermal, intra-peritoneal and peritoneal tissue, and wherein the sensor connector includes a cable that is connected to the sensor.
4. A telemetered characteristic monitor system according to claim 3, wherein the sensor is configured for a wired connection to a characteristic monitor, and wherein the sensor
25 connector of the transmitter device is formed to connect to the configured sensor to obviate the need for a wired connection to the characteristic monitor.
5. A telemetered characteristic monitor system according to claim 1, wherein the sensor is a percutaneous sensor, and wherein the sensor connector includes a cable that is connected
30 to the percutaneous sensor.
6. A telemetered characteristic monitor system according to claim 5, wherein the

percutaneous sensor is configured for a wired connection to a characteristic monitor, and wherein the sensor connector of the transmitter device is formed to connect to the configured percutaneous sensor to obviate the need for a wired connection.

5 7. A telemetered characteristic monitor system according to claim 1, wherein the sensor is a skin surface sensor, and wherein the sensor connector includes a cable that is connected to the skin surface sensor.

8. A telemetered characteristic monitor system according to claim 7, wherein the skin
10 surface sensor is configured for a wired connection to a characteristic monitor, and wherein the sensor connector of the transmitter device is formed to connect to the configured skin surface sensor to obviate the need for a wired connection.

9. A telemetered characteristic monitor system according to claim 1, wherein the
15 transmitter device further includes a receiver to receive data and instructions from the data receiving device.

10. A telemetered characteristic monitor system according to claim 1, wherein the data
receiving device is a data receiver that also provides data to another device.

20 11. A telemetered characteristic monitor system according to claim 1, wherein the data receiving device is an RF programmer for a medical device.

12. A telemetered characteristic monitor system according to claim 1, wherein the data
25 receiving device is a characteristic monitor.

13. A telemetered characteristic monitor system according to claim 1, wherein the data
receiving device is a medication delivery device.

14. A telemetered characteristic monitor system according to claim 13, wherein the
30 medication delivery device is an infusion pump.

15. A telemetered characteristic monitor system according to claim 1, wherein the power

to the sensor is applied through the sensor connector.

16. A telemetered characteristic monitor transmitter device according to claim 1, wherein the telemetered characteristic monitor transmitter is activated by detection of a connection of the sensor to the sensor connector.

17. A telemetered characteristic monitor transmitter device according to claim 1, further including a relay device, between the transmitter and data receiving device, to receive processed signals from the transmitter and relay them to the data receiving device.

18. A telemetered characteristic monitor transmitter device according to claim 17, wherein the relay device increases a maximum distance by amplifying the processed signals from the transmitter to be received by the remotely located data receiving device.

19. A telemetered characteristic monitor transmitter device according to claim 18, wherein the relay device enables the remotely located data receiving device to be located in a different room than the transmitter.

20. A telemetered characteristic monitor transmitter device according to claim 16, wherein the relay device includes a telecommunication device, and wherein when the transmitter generates an alarm which the telecommunication device transmits the alarm to a remotely located receiving station.

21. A telemetered characteristic monitor transmitter device for use in a system with a remotely located characteristic monitor and a sensor producing a signal indicative of a characteristic of a user, the transmitter device comprising:

- a housing;
- a sensor connector coupled to the housing and that is connectable to the sensor to receive the signal from the sensor;
- a processor within the housing coupled to the sensor connector to process the signal from the sensor for delivery to the remotely located characteristic monitor; and

a transmitter coupled to the processor for wirelessly transmitting the processed signals to the remotely located characteristic monitor.

22. A telemetered characteristic monitor transmitter device according to claim 21, wherein
5 the transmitter transmits the processed signals by radio frequencies.

23. A telemetered characteristic monitor transmitter device according to claim 21, wherein
the sensor is implantable in tissue selected from the group consisting essentially of
subcutaneous, dermal, sub-dermal, intra-peritoneal and peritoneal tissue, and wherein the
10 sensor connector includes a cable that is connected to the sensor.

24. A telemetered characteristic monitor transmitter device according to claim 23, wherein
the sensor is configured for a wired connection to a characteristic monitor, and wherein the
sensor connector of the transmitter device is formed to connect to the configured sensor.
15

25. A telemetered characteristic monitor transmitter device according to claim 21, wherein
the sensor is a percutaneous sensor, and wherein the sensor connector includes a cable that is
connected to the percutaneous sensor.

26. A telemetered characteristic monitor transmitter device according to claim 25, wherein
the percutaneous sensor is configured for a wired connection to a characteristic monitor, and
wherein the sensor connector of the transmitter device is formed to connect to the configured
percutaneous sensor to obviate the need for a wired connection.
20

27. A telemetered characteristic monitor system according to claim 21, wherein the sensor
is a skin surface sensor, and wherein the sensor connector includes a cable that is connected to
the skin surface sensor.
25

28. A telemetered characteristic monitor transmitter device according to claim 27, wherein
the skin surface sensor is configured for a wired connection to a characteristic monitor, and
wherein the sensor connector of the transmitter device is formed to connect to the configured
30

skin surface sensor to obviate the need for a wired connection to the characteristic monitor.

29. A telemetered characteristic monitor transmitter device according to claim 21, further including a receiver to receive data and instructions from the characteristic monitor.

5 30. A telemetered characteristic monitor transmitter device according to claim 21, wherein the housing includes a bio-compatible adhesive to secure the housing to a skin surface of the user.

10 31. A telemetered characteristic monitor transmitter device according to claim 30, wherein the bio-compatible adhesive contains an anti-bacterial material.

32. A telemetered characteristic monitor transmitter device according to claim 21, wherein the housing is secured to a skin surface of the user by an adhesive overdressing.

15 33. A telemetered characteristic monitor transmitter device according to claim 21, wherein the housing is less than about 3.0 inches in diameter by 0.5 inches thick.

34. A telemetered characteristic monitor transmitter device according to claim 21, wherein
20 the housing is resistant to fluids when immersed in a fluid.

35. A telemetered characteristic monitor transmitter device according to claim 21, wherein the device is operable in a temperature range of 0°C to 50°C.

25 36. A telemetered characteristic monitor transmitter device according to claim 21, wherein the device has an operable life of at least 3 months.

37. A telemetered characteristic monitor transmitter device according to claim 21, wherein power to the sensor is applied through the sensor connector.

30 38. A telemetered characteristic monitor transmitter device according to claim 21, wherein the telemetered characteristic monitor transmitter is activated by detection of a connection of

the sensor to the sensor connector.

39. A telemetered characteristic monitor transmitter device according to claim 21, further including a relay device, between the transmitter and data receiving device, to receive
5 processed signals from the transmitter and relay them to the data receiving device.

40. A telemetered characteristic monitor transmitter device according to claim 39, wherein the relay device increases a maximum distance by amplifying the processed signals from the transmitter to be received by the remotely located data receiving device.
10

41. A telemetered characteristic monitor transmitter device according to claim 40, wherein the relay device enables the remotely located data receiving device to be located in a different room than the transmitter.

15 42. A telemetered characteristic monitor transmitter device according to claim 39, wherein the relay device includes a telecommunication device, and wherein when the transmitter generates an alarm which the telecommunication device transmits the alarm to a remotely located receiving station.

20 43. A method of calibrating and speeding stabilization of an analyte sensor, the method comprising the steps of:

providing power to the analyte sensor;

applying a high power characteristic to the analyte sensor for a first predetermined period of time; and

25 applying a low power characteristic to the analyte sensor for a second predetermined period of time.

44. The method according to claim 43, wherein the high power characteristic and the low power characteristic are voltages.

30 45. The method according to claim 43, wherein the high power characteristic is a voltage greater than 1.0 volts.

46. The method according to claim 43, wherein the low power characteristic is a voltage less than 0.8 volts.

47. The method according to claim 43, wherein the high power characteristic is a voltage.

48. The method according to claim 43, wherein the low power characteristic is a voltage.

49. The method according to claim 43, wherein the high power characteristic and the low power characteristic are currents.

50. The method according to claim 43, wherein the high power characteristic is a current.

51. The method according to claim 43, wherein the low power characteristic is a current.

52. The method according to claim 43, wherein the first predetermined period of time is between 0.5 to 10 minutes.

53. The method according to claim 43, wherein the first predetermined period of time is under 10 minutes.

54. The method according to claim 43, wherein the second predetermined period of time is under 60 minutes.

55. The method according to claim 43, wherein the second predetermined period of time is under 120 minutes.

56. A telemetered characteristic monitor system for monitoring a characteristic of a user, the system comprising:

a remotely located data receiving device;

a sensor for producing a signal indicative of the characteristic of the user; and

a transmitter device including:

a housing;

a sensor interrogator coupled to the housing and that is optically coupleable to the sensor to receive signals from the sensor;

a processor within the housing coupled to the sensor interrogator to process the signals from the sensor for delivery to the remotely located data receiving device; and

5 a transmitter coupled to the processor for wirelessly transmitting the processed signals to the remotely located data receiving device.

10 57. A telemetered characteristic monitor system according to claim 56, wherein the transmitter transmits the processed signals by radio frequencies.

58. A telemetered characteristic monitor system according to claim 56, wherein the sensor is implantable in tissue selected from the group consisting essentially of subcutaneous, dermal, sub-dermal, intra-peritoneal and peritoneal tissue, and wherein the sensor interrogator includes an optical receiver that optically couples to the sensor.

15 59. A telemetered characteristic monitor system according to claim 56, wherein the transmitter device further includes a receiver to receive data and instructions from the data receiving device.

20 60. A telemetered characteristic monitor system according to claim 56, wherein the data receiving device is a data receiver that also provides data to another device.

61. A telemetered characteristic monitor system according to claim 56, wherein the data receiving device is an RF programmer for a medical device.

25 62. A telemetered characteristic monitor system according to claim 56, wherein the data receiving device is a characteristic monitor.

30 63. A telemetered characteristic monitor system according to claim 56, wherein the data receiving device is a medication delivery device.

64. A telemetered characteristic monitor system according to claim 63, wherein the medication delivery device is an infusion pump.

65. A telemetered characteristic monitor transmitter device according to claim 56, further including a relay device, between the transmitter and data receiving device, to receive processed signals from the transmitter and relay them to the data receiving device.

66. A telemetered characteristic monitor transmitter device according to claim 65, wherein the relay device increases a maximum distance by amplifying the processed signals from the transmitter to be received by the remotely located data receiving device.

67. A telemetered characteristic monitor transmitter device according to claim 66, wherein the relay device enables the remotely located data receiving device to be located in a different room than the transmitter.

68. A telemetered characteristic monitor transmitter device according to claim 56, wherein the relay device includes a telecommunication device, and wherein when the transmitter generates an alarm which the telecommunication device transmits the alarm to a remotely located receiving station.

69. A telemetered characteristic monitor transmitter device for use in a system with a remotely located characteristic monitor and a sensor producing a signal indicative of a characteristic of a user, the transmitter device comprising:

a housing;

a sensor interrogator coupled to the housing and that is optically coupleable to the sensor to receive the signal from the sensor;

a processor within the housing coupled to the sensor interrogator to process the signal from the sensor for delivery to the remotely located characteristic monitor; and

a transmitter coupled to the processor for wirelessly transmitting the processed signals to the remotely located characteristic monitor.

70. A telemetered characteristic monitor transmitter device according to claim 69, wherein the transmitter transmits the processed signals by radio frequencies.
71. A telemetered characteristic monitor transmitter device according to claim 69, wherein
5 the sensor is implantable in tissue selected from the group consisting essentially of subcutaneous, dermal, sub-dermal, intra-peritoneal and peritoneal tissue, and wherein the sensor interrogator includes an optical receiver that is coupleable to the sensor.
72. A telemetered characteristic monitor transmitter device according to claim 69, further
10 including a receiver to receive data and instructions from the characteristic monitor.
73. A telemetered characteristic monitor transmitter device according to claim 69, wherein the housing includes a bio-compatible adhesive to secure the housing to a skin surface of the user.
15
74. A telemetered characteristic monitor transmitter device according to claim 73, wherein the bio-compatible adhesive contains an anti-bacterial material.
75. A telemetered characteristic monitor transmitter device according to claim 69, wherein
20 the housing is secured to a skin surface of the user by an adhesive overdressing.
76. A telemetered characteristic monitor transmitter device according to claim 69, wherein the housing is less than about 3.0 inches in diameter by 0.5 inches thick.
77. A telemetered characteristic monitor transmitter device according to claim 69, wherein
25 the housing is resistant to fluids when immersed in a fluid.
78. A telemetered characteristic monitor transmitter device according to claim 69, wherein the device is operable in a temperature range of 0°C to 50°C.
79. A telemetered characteristic monitor transmitter device according to claim 69, wherein
30 the device has an operable life of at least 3 months.

78. A telemetered characteristic monitor transmitter device according to claim 69, wherein power to the sensor is applied through the sensor connector.


79. A telemetered characteristic monitor transmitter device according to claim 69, further including a relay device, between the transmitter and data receiving device, to receive processed signals from the transmitter and relay them to the data receiving device.

80. A telemetered characteristic monitor transmitter device according to claim 69, wherein the relay device increases a maximum distance by amplifying the processed signals from the transmitter to be received by the remotely located data receiving device.

81. A telemetered characteristic monitor transmitter device according to claim 80, wherein the relay device enables the remotely located data receiving device to be located in a different room than the transmitter.

82. A telemetered characteristic monitor transmitter device according to claim 69, wherein the relay device includes a telecommunications device, and wherein when the transmitter generates an alarm which the telecommunications device transmits the alarm to a remotely located receiving station.

1/5



2/5




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

3/5





FIG. 8B




FIG. 9

4/5

FIG. 10





FIG. 11



HOST INITIATES RF SESSION

TD WAKES UP
THROUGH RBD / INT

TD SIGNALS DATA READY

HOST SENDS COMMAND

TD SENDS STATUS
DATA TO HOST

TD ENABLES RF RECEIVER

TD COLLECTS RF DATA


HOST TERMINATES
RF SESSIONTD CLOSES OUT
RF SESSION AND
GOES TO SLEEP

FIG. 12

5/5




FIG. 13




FIG. 14

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 99/21703

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A61B5/00 A61M5/172

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61B A61M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 95 28878 A (MINIMED INC) 2 November 1995 (1995-11-02)	1-3, 9-14, 21-23, 29, 33-36 56-82
A	page 6, line 1 -page 8, paragraph 2; claims; figures	
X	EP 0 098 592 A (FUJISAWA PHARMACEUTICAL CO) 18 January 1984 (1984-01-18)	1-6, 10, 12-15, 17-19, 21-26, 35-41 56-82
A	page 7, line 15 -page 10, line 8 page 16, line 23 -page 17, line 24 page 19, line 11 -page 22, line 22; claims; figures 1-13	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

1 March 2000

Date of mailing of the international search report

13. 03. 2000

Name and mailing address of the ISA

European Patent Office, P.B. 5816 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Manschot, J

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 99/21703

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 680 727 A (BOEHRINGER MANNHEIM GMBH) 8 November 1995 (1995-11-08) column 7, line 7 -column 8, line 55; claims; figures	1-3, 7-9, 12, 15, 21-23, 27-29, 35-37, 56-59, 62, 69-72, 78
X	US 4 494 950 A (FISCHELL ROBERT E) 22 January 1985 (1985-01-22) column 3, line 55 -column 5, line 55 column 7, line 39 -column 8, line 11; claims; figures	1-6, 13-15, 21-27, 37
X	US 4 935 105 A (CHURCHHOUSE STEPHEN. J) 19 June 1990 (1990-06-19) column 3, line 4 -column 6, line 15 abstract; claims	43-55
A	US 5 411 647 A (JOHNSON KIRK W ET AL) 2 May 1995 (1995-05-02) abstract; claims	43-55

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US 99/21703

Box I Observations where certain claims were found unsearchable (Continuation of Item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of Item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☒ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☒ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claims: 1-42, 56-82

Telemetered characteristic monitor system

2. Claims: 43-55

method of calibrating and stabilization of an analyte sensor

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 99/21703

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9528878 A	02-11-1995	US 5569186 A CA 2165810 A EP 0705071 A	29-10-1996 02-11-1995 10-04-1996
EP 0098592 A	18-01-1984	JP 1648691 C JP 3009750 B JP 59008968 A JP 59016445 A JP 59014857 A EP 0099508 A US 4515584 A US 4636144 A	13-03-1992 12-02-1991 18-01-1984 27-01-1984 25-01-1984 01-02-1984 07-05-1985 13-01-1987
EP 0680727 A	08-11-1995	DE 4415896 A AU 674474 B AU 1763495 A CA 2148569 A CN 1128353 A FI 952131 A HU 75243 A IL 113569 A JP 7311196 A KR 163476 B NO 951754 A NZ 272000 A US 5507288 A ZA 9503585 A	09-11-1995 19-12-1996 07-12-1995 06-11-1995 07-08-1996 06-11-1995 28-05-1997 04-01-1998 28-11-1995 15-12-1998 06-11-1995 24-04-1997 16-04-1996 04-11-1996
US 4494950 A	22-01-1985	NONE	
US 4935105 A	19-06-1990	AU 1212988 A DE 3805773 A FR 2611272 A GB 2201248 A,B IT 1215946 B JP 1219661 A	25-08-1988 22-09-1988 26-08-1988 24-08-1988 22-02-1990 01-09-1989
US 5411647 A	02-05-1995	AU 5185093 A BR 9304788 A CA 2103325 A CN 1103488 A EP 0601720 A EP 0933430 A IL 107700 A JP 6242055 A ZA 9308555 A	02-06-1994 14-06-1994 24-05-1994 07-06-1995 15-06-1994 04-08-1999 23-07-1996 02-09-1994 02-08-1994